

# ETIQUETTE



0845 222 0354



sales@etiquette.co.uk



www.etiquette.co.uk

## TTP-245C SERIES



The ETIQUETTE TTP-245C Series of Desktop Thermal Printers offer the high performance and low cost that Etiquette customers have come to expect. With a new smaller footprint, the TTP-245C Printer is built to the highest standards of durability and reliability whilst providing the best value compared to rival printers in its market. If you need to print 4-inch wide labels, tags, and other media, the TTP-245C Printer from ETIQUETTE is the ideal solution.



**FREE**  
Full Professional  
Labelling Software  
with every  
**ETIQUETTE** Printer

The ETIQUETTE TTP-245C Printers feature fast 6-inch-per-second print speeds to meet your low to medium volume label printing applications. Its 200MHz 32-Bit Processor increases your productivity with fast 'first label out' and no between label delays even when taking advantage of its internally scalable True Type fonts. Add a standard internal Ethernet port and this printer is easily integrated into any application.

The easy to use design provides simple, fast ribbon and media loading and with ETIQUETTE's smallest footprint ever for a 4-inch desktop printer, the TTP-245C Series easily fits into your most congested workspace.

All ETIQUETTE Printers are supplied complete with LabelDirect® Professional Labelling Software that includes advanced features such as print job management and datastore. Designed specifically for the ETIQUETTE Printer range and driving the printer 'directly' in native command language, it is 100% WYSIWYG and produces print performance that cannot be beaten



#### Features:

- 8MB SDRAM and 2MB Flash Memory
- 6 inch/sec Print Speed
- Ribbon Capacity – 110mm
- Label Capacity – 127mm
- 18 Month Warranty



PRINTER	<ul style="list-style-type: none"> <li>• TTP-245C</li> </ul>
RESOLUTION	<ul style="list-style-type: none"> <li>• 203 DPI</li> </ul>
PRINTING METHOD	<ul style="list-style-type: none"> <li>• THERMAL TRANSFER &amp; DIRECT THERMAL</li> </ul>
PRINT SPEED	<ul style="list-style-type: none"> <li>• Up to 6 IPS</li> </ul>
MAX. PRINT WIDTH	<ul style="list-style-type: none"> <li>• 108mm (4.25")</li> </ul>
MAX. PRINT LENGTH	<ul style="list-style-type: none"> <li>• 2286mm (90")</li> </ul>
ENCLOSURE	<ul style="list-style-type: none"> <li>• Double Walled Plastic</li> </ul>
PHYSICAL DIMENSION	<ul style="list-style-type: none"> <li>• 258mm (L) x 202mm (W) x 173mm (H)</li> </ul>
LABEL ROLL CAPACITY	<ul style="list-style-type: none"> <li>• 127mm (5") OD</li> </ul>
PROCESSOR	<ul style="list-style-type: none"> <li>• 32-Bit RISC CPU</li> </ul>
MEMORY	<ul style="list-style-type: none"> <li>• 2MB Flash Memory</li> <li>• 8MB SDRAM</li> <li>• SD Card Slot for Memory Expansion</li> </ul>
INTERFACE	<ul style="list-style-type: none"> <li>• RS-232C</li> <li>• Centronics</li> <li>• USB 2.0</li> <li>• Internal Ethernet</li> </ul>
POWER	<ul style="list-style-type: none"> <li>• External Universal Switching Power Supply</li> </ul>
OPERATION SWITCH, BUTTON, LED	<ul style="list-style-type: none"> <li>• One Power Switch</li> <li>• One Feed Button</li> <li>• One LED (3 colours – Green, Amber, Red)</li> </ul>
SENSORS	<ul style="list-style-type: none"> <li>• Gap Transmissive Sensor</li> <li>• Moveable Black Mark Reflective Sensor</li> <li>• Head Open Sensor</li> <li>• Ribbon Encoder Sensor</li> </ul>
INTERNAL FONT	<ul style="list-style-type: none"> <li>• Eight Alpha-Numeric Bitmap Fonts</li> <li>• One Monotype Imaging CG Triumvirate Bold Condensed Scalable Font</li> <li>• Built-In Monotype True-Type Font Engine</li> </ul>
BARCODE	<ul style="list-style-type: none"> <li>• 1D Barcode – Code 39, Code 93, 128UCC, Code 128 Subset A, B, C, Codabar, Interleave 2 of 5, EAN-8, EAN-13, EAN-128, UPC-A, UPC-E, EAN and UPC 2 (5) digits add-on, MSI, PLESSEY, POSTNET</li> <li>• 2D Bar Code – PDF-417, Maxicode, Datamatrix, QR Code</li> </ul>
FONT & BARCODE ROTATION	<ul style="list-style-type: none"> <li>• 0, 90, 180, 270 Degrees</li> </ul>
PRINTER LANGUAGE	<ul style="list-style-type: none"> <li>• TSPL-EZ</li> </ul>
MEDIA TYPE	<ul style="list-style-type: none"> <li>• Continuous, die-cut, tag, fan-fold &amp; Linerless (DT Only)</li> </ul>
MEDIA WOUND TYPE	<ul style="list-style-type: none"> <li>• Outside Wound</li> </ul>
MEDIA WIDTH	<ul style="list-style-type: none"> <li>• 25.4m – 118mm (1.0" – 4.6")</li> </ul>
MEDIA THICKNESS	<ul style="list-style-type: none"> <li>• 0.06 – 0.19mm (2.3-7.4mil)</li> </ul>
MEDIA CORE DIAMETER	<ul style="list-style-type: none"> <li>• 25.4mm (1") &amp; 38.1mm (1.5")</li> </ul>
ENVIRONMENT CONDITION	<ul style="list-style-type: none"> <li>• Operation : 5-40°C, 25-85% Non Condensing</li> <li>• Storage : -40°C – 60°C, 10-90% Non Condensing</li> </ul>
SAFETY REGULATION	<ul style="list-style-type: none"> <li>• FCC Class B, CE Class B, C-Tick Class B, UL, CUL, TUV/GS, CCC</li> </ul>
ACCESSORIES	<ul style="list-style-type: none"> <li>• LabelDirect® Labelling Software</li> <li>• Quick Start Guide</li> <li>• USB Cable</li> <li>• External Universal Switching Power Supply</li> <li>• Power Cord</li> </ul>
FACTORY OPTION	<ul style="list-style-type: none"> <li>• Real Time Clock</li> </ul>
OPTIONS	<ul style="list-style-type: none"> <li>• Peel off Module Assembly</li> <li>• Guillotine Cutter</li> <li>• Keyboard Display Unit</li> <li>• Contact CCD Barcode Scanner</li> <li>• Long Range Linear Image Bar Code Scanner</li> <li>• External Wireless (802.11bg) Print Server</li> </ul>